

MDF30-42-12

Direct Drive 380V Automation for Sprung Roller Shutters



DIRECT DRIVE
Quality High Use Automation
For Spring Balanced
Roller Shutters

FEATURES

- Integrated Limit Switches
- Crank or Chain Manual Override Options
- Integrated Safety Catch
- Robust, Strong & Durable
- Wide Range of Control Options
- 3 Phase 380V
- Thermal Overload Protection
- Higher Torque Models available up to 2000 Nm

SPECIFICATIONS

| | |
|----------------|---|
| VOLTAGE | 380V AC @ 50 Hz (Three Phase) |
| CURRENT INPUT | 5.7 A |
| TORQUE | 420 Nm |
| MOTOR OUTPUT | 1.1 kW |
| SPEED | 12 Rpm |
| DUTY CYCLE | 20 operations / Hour (Dependent on door size) |
| SHAFT DIAMETER | 40 mm (8mm keyway) |
| PROTECTION | IP54 |
| DIMENSIONS | 507 x 122 x 287mm |
| WEIGHT | 27 Kg |

(The Company reserves the right to amend product specifications and information without notice.)

PLEASE CONTACT OUR SALES TEAM +(27) 31 700 8260 for further information.

PART OF THE MARANTEC COMPANY GROUP
OPENING DOORS IN SOUTH AFRICA

PROUD SUPPORTERS AND SUPPLIERS OF

